



B-LOC B112 Ø120xØ165
 (Inverted inner/outer rings)
 TRANSMISSIBLE TORQUE= 26,280 ft-lb
 TIGHTENING TORQUE = 105 ft-lb
 (SUPPLIED BY TORQUE TECH.)

Par de embrague CLUTCH TORQUE	Nm	20000	22600
Par de freno BRAKE TORQUE	Nm	19000	19000
Presion OPERATION AIR PRESS.	Bar	5.5	5.86
Velocidad max. MAX. SPEED	Rpm	850	
Peso total TOTAL WEIGHT	Kg	325	

Conexion CONNECTION	C
Pl. mec.:	587614W

J	INTER.	Kgm ²	12.2
	EXTER.	Kgm ²	4.97
Vol.cilind. CYLINDER VOLUME	Vol.nuevo NEW VOLUME	dm ³	3.21
	Vol.max.desg. MAX. WEAR V.	dm ³	5.23

MULTZOA									
ZENB. Nº	IZENDAPENA Denominación	KOPURUA Cant.	MATERIALA Material	KODEA Código	DIMENTSIOAK Dimensiones	TRATAMENDUA Tratamiento	PISUA Peso		
IZENAK esquinas TXOKOKAK rincones	R = 0,5 R = 0,8		ALDAKETA Modificación	DATA Fecha	IZENA Nombre	MARRAZTUA Dibujoa	SINADURA Firma	DATA Data	
PERDOIARIK GABEKO NEURRIAK Medidas sin tolerancia DIN 7168						EGIAZTATUA Comprobado	A.A.	2008/04/22	
NEURRIA Medida	PERDOIA Tolerancia					PLANOAREN ZENB. Plano Nº:	58376454AB		
0,5 - 6	± 0,1					ESKALA Escala	1:5		
6 - 30	± 0,2								
30 - 120	± 0,3								
120 - 315	± 0,5								
315 - 1000	± 0,8								
BALAZTA-ENBRAGE PNEUMATIKOA FRENO ENBRAGE NEUMATICO						GOIZPER			



Torque Technologies, the exclusive U.S. Stocking agency of GOIZPER Clutches and Brakes provides expert, computerized application engineering and retrofit services to customers across the USA.

For drawings, specifications and questions regarding a GOIZPER Clutch-Brake, please contact us:

Toll-Free: 1-800-813-0844 Web: www.goizperusa.com
 Phone: 1-941-358-9447 Email: sales@goizperusa.com
 Fax: 1-941-358-9647