



Locking ring.
Installing torque:
108 Nm (80 Ft Lb)
Transmissible torque:
Ta= 25868 Nm (19080 Ft Lb)

Par de embrague CLUTCH TORQUE	N m	14060
Par de freno BRAKE TORQUE	N m	18250
Presión OPERATION AIR PRESS.	Bar	5.1
Velocidad max. MAX. SPEED	Rom	750
Peso total TOTAL WEIGHT	Kg	262
J	INTER.	Kg m ² 10.5
	EXTER.	Kg m ² 3.34
Vol. cil/Ind. CYLINDER VOLUME	Vol. nuevo NEW VOLUME	dm ³ 2.84
	Vol. max. desg. MAX. WEAR V.	dm ³ 5.2

MULTZOA CONJUNTO		KOPURUA Cont.		MATERIALA Material	KODEA Código	DIMENTSIOAK Dimensiones	TRATAMENDUA Tratamiento	PISUA Paso
ZENB. Nº	IZENPENA Denominación	ALDAKETA Modificación		DATA Fecha	IZENA Nombre	MARRAZTUA Dibujado	SINADURA Firma	DATA Data
PERDOIARIK GABEKO NEURRIARIK Medidas sin tolerancia DIN 7168						EGIAZTATUA Comprobado	J.M.I.	2010/03/29
NEURRIA Medida	PERDOIARIA Tolerancia					PLANOAREN ZENB. Plano Nº.	57676486AD Marketing	
0.5 - 6	± 0.1					ESKALA Escala	1:4	
6 - 30	± 0.2					GOIZPER		
30 - 120	± 0.3							
120 - 315	± 0.5							
315 - 1000	± 0.8							
BALAZTA-EMBRAGE PNEUMATIKOAK FRENO EMBRAGUE NEUMATICO								



Torque Technologies, the exclusive U.S. Stocking agency of GOIZPER Clutches and Brakes provides expert, computerized application engineering and retrofit services to customers across the USA.

For drawings, specifications and questions regarding a GOIZPER Clutch-Brake, please contact us:

Toll-Free: 1-800-813-0844 Web: www.goizperusa.com
Phone: 1-941-358-9447 Email: sales@goizperusa.com
Fax: 1-941-358-9647